

WDL-1500MFM

15" Flush Mount LCD Monitor



SPECIFICATION

Display

Screen size	15" (diagonal)
Viewing size	304.13(H) × 228.1(V)(mm)
Resolution	1024(H) × 768(V)
Brightness	250cd/m ²
Viewing angle	Up : 80° / Down : 80° / Right : 85° / Left : 85°
Contrast ratio	700:1
Display colors	16.7M colors
Pixel format	RGB vertical strip
System compatibility	PC : VESA standard VGA to XGA 60Hz Video : NTSC / PAL / SECAM (auto detection)
Plug & play support	DDC 1/2B
Pixel pitch	0.297(H) × 0.297(V)(mm)
Response time	8ms
Frequency	Horizontal : 31.5~37.5KHz / Vertical : 56~75Hz
OSD controls	Auto adjust, brightness & contrast, size & positon, color control, language selection, OSD position, video control, input selection
Wall mounting	Yes

Video/Audio Input

Video input	D-SUB 15P, HDMI, Video 1, 2 BNC
Audio input	RCA, Ø3.5 Stereo phone jack

Video/Audio Output

Video output	BNC Video Monitor output
Audio output	Ø3.5 Stereo phone jack Audio Lineout

Power

Input	DC 12V
Power management	VESA DPMS
Power consumption	Normal mode : T.B.D / DPMS mode : < 4W
Power supply	Input : AC 100~240V, 50~60Hz / Output : DC 12V, 5.0A

Environmental

Operating temperature	0°C ~ +50°C (+32°F ~ +122°F)
Storage temperature	-20°C ~ +60°C (-4°F ~ +140°F)
Operating humidity	30%~60%
Storage humidity	5%~70%

Dimensions

Dimensions	436.0(W) × 367.0(H) × 42.0(D)(mm)
------------	-----------------------------------

Weight	T.B.D
--------	-------

FEATURES

On-screen menu display for feature and video adjustments

Power supply included

DIMENSIONS

