

DECKING QLD SPECIES

Parkside decking is perfect in any decking application. It adds beauty, richness and depth to any commercial or residential application.

KEY BENEFITS

- Our products are grown, produced and manufactured in Australia for Australian conditions.
- Parkside decking heartwood is naturally insect and decay resistant, and every piece is treated with an ACQ H3 treatment, ensuring any sapwood that is used is also fully durable.
- Our QLD species are all durability Class 1 above ground species.
- Parkside Timber is Australia's largest producer of Spotted Gum.
- Our decking is certified by internationally recognised PEFC, denoting that all products are sourced from sustainably managed forests.

COMMERCIAL & STRUCTURAL

- Parkside decking can be used in the construction of timber decks, boardwalks, bridges and jetties, as well as a vast array of other platform and structural applications.
- Commercial decking is available in large section sizes in dressed or rough sawn and features the highest strength group rating for superior span capacity.
- All Parkside decking timbers are manufactured to Australian Standards AS 2796.

PERFORMANCE

When correctly installed and maintained, our timbers are able to perform its intended function for the design life of that component. Refer to Parkside Decking Installation Guide for handling, storage, installation and maintenance.



SPECIES



QLD Spotted Gum
Hardness 11



Grey & Red Ironbark
Hardness 14



QLD Reds
Hardness 12



Mixed Blends
Hardness 10.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



GRADES

Select | Standard | Feature



SIZES AND LENGTHS

65 | 86 | 135 x 19mm

135 x 32mm

140 x 25mm

Random packs 1.5m to 5.7m



DURABILITY

Class 1 (Above Ground)

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959-2009 and BAL 19 as a minimum

Spotted Gum and Ironbark Red are fire rated to BAL 29

Chain of Custody as per AS 4707-2008 PEFC / AFS



**PARKSIDE
TIMBER**



**Responsible
Wood**
RW/1-31-57