# DECKING VIC & WA SPECIES

Parkside decking is perfect in any decking application. It adds beauty, richness and depth to any commercial or residential application.

#### **KEY BENEFITS**

- Our products are grown, produced and manufactured in Australia for Australian conditions.
- Our VIC and WA species are all durability Class 2 above ground species.
- Parkside Silvertop decking is a beloved product for fire exposed areas due to its BAL 29 rating. This means the product is deemed to satisfy the requirements for bushfire prone areas under AS 3959.
- Our decking is certified by internationally recognised PEFC, denoting that all products are sourced from sustainably managed forests.

#### **COMMERCIAL & STRUCTURAL**

- Parkside decking can be used in the construction of timber decks, boardwalks, bridges and jetties, as well as a vast array of other platform and structural applications.
- Commercial decking is available in large section sizes in dressed or rough sawn and features the highest strength group rating for superior span capacity.
- All Parkside decking timbers are manufactured to Australian Standards AS 2796.

## **PERFORMANCE**

When correctly installed and maintained, our timbers are able to perform its intended function for the design life of that component. Refer to Parkside Decking Installation Guide for handling, storage, installation and maintenance.



#### **SPECIES**



Silvertop Ash (VIC) Hardness 9.5



Karri (WA) Hardness 9.0



Jarrah (WA) Hardness 8.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



#### **GRADES**

Select I Standard I Feature



#### SIZES AND LENGTHS

65 | 86 | 135 x 19mm 135 x 32mm (Silvertop Ash) Random packs 1.5m to 5.7m



# **DURABILITY**

Class 2 (Above Ground)



### **CERTIFICATION**

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959-2009

Silvertop Ash is rated to BAL 29

Karri and Jarrah can achieve BAL 29 when used in conjunction with non-combustible wall cladding and enclosed subfloor

Chain of Custody as per AS 4707-2008 PEFC / AFS



