




BARI

STONE POLYMER COMPOSITE

TECHNICAL DATA SHEET




Bella Flooring
GROUP

BARI

STONE POLYMER COMPOSITE

TECHNICAL DATA SHEET



Bella Flooring GROUP

PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Bari Collection
Construction	Stone Polymer Composite
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	4.8mm (0.1890")
Wear Layer	12mil (0.30mm)
Underlayment	1.5mm IXPE with embossed (0.0591")
Edge Profile	Micro Bevel
Surface Finish	UV / Ceramic Bead
Embossing	Photo Match Embossing
Edge Profile	Easy-to-install with Valinge 2G
Size	7" W x 48" L (180x1220mm)
SQ. Feet Per Carton	23.9 SQFT/CTN
Pieces Per Carton	10 PIECES/CTN
Weight Per Carton	33.43 LBS/CTN
Carton Per Pallet	65 CTNS/PLT
Installation Method	Floating / Glue Down



TECHNICAL PROPERTIES




Dimensional Stability	ASTM F2199 Passes $\leq 0.2\%$ / lineal ft. (305 mm)
Curling	ISO 23999 Passes $\leq 2\text{mm}$
Static Load	ASTM F970 Passes $\leq 0.005"$ (0.13mm) (without underlayer)
Static Load Limit	SIM Test Passes 1000 psi (0.02mm) (without underlayer)
Residual Indentation	ASTM F1914 Passes Average: $\geq 0.007"$ (0.18mm) (without underlayer)
Resistance to Chemicals	ASTM F925 Passes No more than a slight change in surface
Resistance to Heat	ASTM F1514 Passes Average $\Delta E < 8.0$
Resistance to Light	ASTM F1515 Passes Average $\Delta E < 8.0$
Critical Radiant Flux	ASTM E648 Passes Class I: $\geq 0.45 \text{ W/Sq.cm}$
Smoke Density	ASTM E662 Passes Flaming & Non Flaming ≤ 450
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method v1.2 Compliant V1.2-2017
Substances of Very High Concern	REACH SVHC 191 Passes Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 Passes
Phthalates	ASTM D7823 Passes CPSC-CH-C1001-9.3
Slip Resistance	ASTM D2047 Passes Dry: 0.38 Wet: 0.90
Fungi Resistance	ASTM G21-15 Passes
IIC Rating	ASTM E492 & ASTM E989 Result: 66
STC Rating	ASTM E90 & ASTM E413 Result: 68

SUSTAINABILITY & WARRANTIES



Material	Virgin Vinyl
Certification	Floor Score® Certified
Environmental Product Declaration	EPD Vinyl Click
Health Product Declaration	HPD 2.1 Vinyl Click - 1000 ppm

Warranties	Lifetime Residential & 20-Year Commercial
------------	---



Bella Flooring GROUP



100% WATERPROOF

BARI

EASY INSTALL

STONE POLYMER COMPOSITE LUXURY FLOORING



NATURA



SIX UNIQUE COLORS AVAILABLE



RUSTIO BIANCA



NUBE



CLASSICO



NUVOLA BIANCA



NATURA



CANNELLA

DIMENSIONS	7" X 48"
TOTAL THICKNESS	4.8 MM
WEAR LAYER	12 MIL / .30 MM
EDGE PROFILE	MICROBEVEL
ATTACHED PAD	1.5 MM IXPE
SQUARE FEET PER CARTON	23.90
CARTONS PER PALLET	65
SQUARE FEET PER PALLET	1,553.51
LOCKING SYSTEM	Valinge 2G

CORRESPONDING TRANSITIONS

Add a touch of finished perfection to every installation with exact color matched transitions.




END CAP



T-MOULDING



REDUCER



FLUSH
STAIR NOSE

NEED
ADDITIONAL
DETAILS?

Scan this QR code with your smart device's camera to visit this product's page on our website.

