



EVE P-140 VW

EVE P-140 VW is a variable white wash light featuring cool white, warm white and amber LEDs. EVE P-140 VW is a [D-fi USB](#) compatible fixture providing the option to control the fixture wirelessly in master/slave mode or with DMX control. This sturdy wash light has a built-in gel frame holder and a 6 ¼ - inch accessory slot to hold optional barn doors. EVE P-140 VW comes with interchangeable lenses that attach magnetically to alter the beam for added lighting flexibility. PowerCON power connections means secure power connections and power linking. The fixture operates silently due to its fanless design and its flicker-free output make EVE P-140 VW perfect for on-camera use. Both 3- and 5-pin DMX connectors provide added control connection flexibility.



Specifications

- DMX Channels: 3 or 9
- DMX Connectors: 3- and 5-pin XLR
- Light Source: 40 LEDs (13 cool white, 13 warm white, 14 amber) 140 W total, (2.4 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 34 Hz
- PWM Frequency: 2 kHz
- Beam Angle: 35°, 41° or 56°
- Field Angle: 63°, 94° or 82°
- Illuminance: (35°): 2,793 lux @ 2 m (lens 1)
(41°): 2,082 lux @ 2 m (no lens installed)
(56°): 1,335 lux @ 2 m (lens 2)
(37°): 447 lux @ 5 m (lens 1)
(41°): 333 lux @ 5 m (no lens installed)
(56°): 214 lux @ 5 m (lens 2)
- Power Linking: 8 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 122 W, 1.2 A @ 120 V, 60 Hz
111 W, 0.5 A @ 230 V, 50 Hz
- Weight: 7.6 lbs. (3.5 kg)
- Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)
- Approvals: CE, MET
- Color Temperature Range: 2700 to 13000 K
- Optional Controllers: [D-Fi USB](#)
- Accessory Holder/Gel Frame Size: 6.25 in (159 mm)
- CRI: 77

What's Included

- Lens 1 and Lens 2