



COLORado 2 Solo

COLORado 2 Solo is fitted with three 40 W RGBW LEDs to project a beautiful and fully homogenized beam through fast and smooth zoom and precision optics. This indoor/outdoor wash light has IP rated power and data connectors, and full convection cooling to ensure a reliable and silent performance in a wide range of applications, from theatrical stages to outdoor festival productions.



Specifications

Optical

- Light Source: 3 LEDs (quad-color RGBW) 40 W, (2.5 A), 50,000 hours life expectancy
- Beam Angle: 5° to 27°
- Field Angle: 7° to 42°
- Zoom Range: 5° to 42°
- Illuminance (5°): 9,720 lux @ 5 m
- Illuminance (27°): 318 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 2400 Hz, 6000 Hz, 25,000 Hz

Construction / Physical

- Dimensions: 8.26 x 10.7 x 15.2in (210 x 274 x 387 mm)
- Weight: 16.2lb (7.3kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 7.5 in (190 mm)

Certifications / Qualifications

- CE, MET
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 5
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes

Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)