

Color Force 72™

Product Code	CHCF72NFRGBA
Net Dimensions	1,759mm x 182mm x 177mm / 69.25" x 7.25" x 7"
Net Weight	22kgs / 48lbs
Power Input Rating	100-240V AC, 50-60 Hz, 700VA
Control Protocol	ANSI E1.11 USITT DMX 512-A
Cooling System	Forced - 2x fans
Construction	Anodised aluminium extrusion
Built-In Hardware	Quick release lever for tilt adjustment
IP Rating	IP20
Approvals	CISPR 22 :2006/EN55022 :2006 & CISPR 24 :1997/ EN55024 :1998, ICES-003 :2004 & FCC Part 15 Subpart B: 2007, CSA C22. No. 166-M1983:R2008 UL 1573:2003; UL 8750

LEDs	12 LED engines, 24 (6 x RGBA) LEDs, 288 total LEDs
Control Modes	43 channels Fx HSI 36 channels HSI 36 channels RGB (*Magic Amber) 48 channels RGBA 49 channels sRGBI (*Magic Amber) 9 channels Fx HSI 3 channels HSI 3 channels RGB 4 channels RGBA 5 channels sRGBI (*Magic Amber) 1 channel DMX Look Select
Dimming Curve	Theatrical
Variable Effects Engine	Yes
Lumen Output	White 8,000 / 12,000 hot lumens (prelim.)
Optics	Specialised close focus lens
Beam Angle	23° (approx.)
Beam Distribution	Asymmetrical direct illumination
CCT	Adjustable 1,000 - 10,000K
CRI	92
Colour Gamut	Performance enhanced
Lamp Life	L70 at 50,000 hours