

Expanse Tile 536 Waterproof Floating Floor

StoneCast
RIGID LUXURY FLOOR



Size
12" x 36" *nominal* (30.5 cm x 91.5 cm)
5.7 mm thick

Wear Layer
20 mil / UV-Cured Urethane

Edge Treatment
Four-Sided Color-Enhanced Bevel

Installation
Floating Floor, Fold-Down,
Drop Lock System
(on, above or below grade)

Coordinating Moldings
See nextfloor.net for more details.

Packaging
8 pieces per carton (40 lbs)
24.1 SF per carton
54 cartons per pallet
19 pallets per container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM D2047	Passes > 0.6
Static Load Limit	ASTM F970	exceeds 3000 lbs
Sound Transmission Class (STC)	ASTM E492	64 <i>without cushion</i>
Impact Isulation Class (IIC)	ASTM E989	73
High Frequency Impact Isulation Class (HIIC)	ASTM E3222	89
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		



Warranties
Lifetime Waterproof
Lifetime Residential Wear
30-Year Commercial Wear
See full warranty text at nextfloor.net