

# Incredible 5.0 525 Waterproof Floating Floor



**Size**  
7" x 48" nominal (18 cm x 122 cm)  
5.0 mm thick

**Wear Layer**  
12 mil / UV-Cured Urethane

**Edge Treatment**  
Four-Sided Microbevel

**Installation**  
Angle-Angle Click Floating Floor  
(on, above or below grade)

**Attached Cushion**  
For superior sound abatement and easier installation

**Coordinating Moldings**  
See [nextfloor.net](http://nextfloor.net) for more details.

**Packaging**  
12 pieces per carton (42 lbs)  
28.4 SF per carton  
55 cartons per pallet  
18 pallets per container

**Testing**  
Critical Radiant Flux  
Surface Flammability  
Coefficient of Friction  
Static Load Limit  
Sound Transmission Class (STC)  
Impact Isulation Class (IIC)  
High Frequency Impact Isulation Class(HIIC)  
Floor Score Certified  
Phthalate Free  
100% Virgin PVC

**Warranties**  
Lifetime Waterproof  
Lifetime Residential Wear  
10-Year Commercial Wear  
See full warranty text at [nextfloor.net](http://nextfloor.net)

ASTM E648	Class I
DOC FF 1-70	Passed
ASTM 2047	Passes>0.6
ASTM F970	exceeds 3000 lbs <small>without cushion</small>
ASTM E492	64
ASTM E989	71
ASTM E3222	88



**Sample SKUs**  
**Handle Boards**  
HB525NF-B  
10 per carton (126 lbs)

**Strap Sets**  
SS525NF-B  
5 per carton (37.5 lbs)

**Step Up Display**  
8CARDS525NF-1B  
8CARDS525NF-2B  
FIXT525NF  
Packaged in 3 cartons (165 lbs)