



## RENTAL PACKAGE

### 600,000 BTU Make-Up Air Heater

**TECHNICAL SPECIFICATIONS:**

Model.....MUA600  
 Dimensions  
 Length.....60.5"  
 Width.....29.25"  
 Height..... 48"  
 Shipping Weight ..... 500 lbs.  
 Duct Connection.....20" Outlet Flange  
 Power Supply.....115 volt/1 phase/60HZ

**APPLICATIONS:**

- Job Site/Construction Heat
- General/Building Heat
- Temporary Shelter
- Industrial Heat
- Commercial/Institutional Heating

**TECHNICAL DATA:**

<b>Electrical Data</b>	1.5 HP 12 FLA 20 amps
<b>Fuel</b> Type Consumption rate Burner type Inlet pressure Maximum manifold pressure Minimum gas supply	Natural Gas/Propane 100,000 BTU/hr (min) / 600,000 BTU/hr (max) Modulating Inlet pressure (min/max): 5 in. wc (min) / 2 psi (max) 5 in wc 7 in wc for maximum input adjustment
<b>Blower</b> Speed Drive mechanism Duct outlet	3500 CFM Belt Drive 20" diameter outlet flange
<b>Heat</b> Thermostat Maximum temperature rise Maximum discharge temperature	Remote/Stationary 240° F 220° F
<b>General</b> Body Mobility Portability	Stainless steel construction 8" lockable castors Fork lift pockets/Lifting eye

Consult your TCRS rental representative for more details.

©2021 TCRS  
 All rights reserved.  
 Materials and specifications are subject to change without notice.