



HYDRAULIC HAMMERS

| MODEL NUMBER | OPERATING WEIGHT LB (KG) | ENERGY CLASS FT-LB | TOOL DIAMETER IN (MM) | OIL FLOW GPM (LPM) | OPERATING PRESSURE PSI (BAR) | IMPACT RATE BPM | CARRIER WEIGHT LBS (TON) |
|---------------------|---|-------------------------------|--------------------------------------|-----------------------------------|---|----------------------------|---|
| AB 307 | 664 (301) | 550 | 2.75 (70) | 9-19 (35-70) | 1600-2400 (110-165) | 380-1000 | 6600-14300 (3.0-6.5) |
| AB 408 | 950 (431) | 800 | 2.95 (75) | 10-20 (40-80) | 1740-2390 (120-165) | 380-900 | 9900-17600 (4.5-8.0) |
| AB 509 | 1105 (495) | 1000 | 3.15 (80) | 12-24 (45-90) | 2030-2470 (140-170) | 400-1100 | 9900-20000 (4.5-9.0) |
| AB 610 | 1343 (609) | 1400 | 3.54 (90) | 13-26 (50-100) | 2030-2470 (140-170) | 350-1000 | 13200-22000 (6.0-10.0) |
| AB 1015 | 2324 (1054) | 2500 | 4.13 (105) | 21-37 (80-140) | 2030-2610 (140-180) | 350-900 | 22000-33000 (10-15) |
| AB 1218 | 2860 (1297) | 3500 | 4.52 (115) | 26-40 (100-150) | 2330-2755 (140-180) | 320-700 | 26400-39600 (12-18) |
| AB 1824 | 3940 (1787) | 4500 | 5.31 (135) | 32-45 (120-170) | 2320-2760 (160-190) | 320-800 | 39600-52800 (18-24) |
| AB 2026 | 4332 (1965) | 5500 | 5.31 (135) | 37-50 (140-190) | 2320-2760 (160-190) | 340-800 | 44000-57200 (20-26) |
| AB 2230 | 4670 (2118) | 6500 | 5.70 (145) | 40-55 (150-210) | 2320-2760 (160-190) | 300-720 | 48000-66000 (22-30) |
| AB 2842 | 6984 (3168) | 8000 | 6.10 (155) | 53-69 (220-260) | 2320-2760 (160-190) | 230-600 | 61600-92400 (28-42) |
| AB 3450 | 7961 (3611) | 10000 | 6.50 (165) | 58-74 (220-280) | 2320-2760 (160-190) | 230-600 | 74800-110000 (34-50) |
| AB 4060 | 9222 (4183) | 12000 | 6.90 (175) | 63-84 (240-320) | 2320-2760 (160-190) | 230-550 | 88000-132000 (40-60) |
| AB 4580 | 10344 (4692) | 14000 | 7.08 (180) | 69-95 (270-370) | 2320-2760 (160-190) | 270-550 | 99000-176000 (45-80) |

- Silenced - Enclosed Bracket
- Stroke Adjuster (variable speed control)
- Anti Blank Fire
- On Board Shock Damping
- Auto Lube Systems Available
- Two Moving Parts
- Oversized Accumulator (protects hydraulic circuit)
- Oversized Tie Rods (longer lasting)
- 550 to 14,000 ft-lb models available
- Fits 3 to 80 ton carriers

REBEL ATTACHMENTS

BY ALLIED PEDESTAL BOOM SYSTEMS

(419) 663-1048 | Norwalk, OH | alliedpbs.com

75 Commons Drive, Norwalk, OH 44857