



## Product Information Flyer

### MILPRO<sup>®</sup> WAY OILS

#### DESCRIPTION

MILPRO LUBRICANTS are clear colored lubricating oils designed to reduce friction and “stick-slip” on machine tool slide-ways. They provide a uniform oil film that insures smooth table motion even after extended shutdowns. MILPRO WAY LUBRICANTS are fortified with extreme pressure and tackiness additives to reduce metal-to-metal wear. MILPRO WAY LUBRICANTS provide trouble-free lubrication on all plain bearing slide-ways regardless of table load or way speed.

### MILPRO WAY 32 MILPRO SURE-WAY 68 MILPRO WAY 220

Physical Specifications	<u>Way 32</u>	<u>Sure-Way 68</u>	<u>Way 220</u>
Cincinnati Milacron Lubricants	P-53	P-47	P-50
ISO Grade	32	68	220
Viscosity, SUS at 100°F	160	320	1230
Density (#/gal)	7.5	7.6	7.7
Sp. Gravity	0.90	0.908	0.93
API Gravity	26.5	30.2	20.8
Flash Point, °F	275	330	325

MILPRO Way Oils are recommended to be used in accordance with good machine maintenance and hygiene practices and should be changed as required. Products were formulated to conform to Cincinnati Milacron Lubricant specifications.

**Limitation of Liability:** Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY  
10200 ALLIANCE DR.  
BLUE ASH, OHIO 45242  
1-888-246-2665