



Dry Miter Cutter 9410 ND - the versatile with Ø 255/60T CT saw blade



- The precise miter saw for metal: Ideal for cutting tubes and profiles made of stainless steel, steel, non-ferrous metal, plastic and composite materials
- The solution for dry wall construction!
- Fine cuts in soft and sensitive materials
- No need of lubricant and manual deburring
- Adjustable miter cut from -45° to + 45° (stepless)
- Secure fixing with double 3-step quick release system
- Robust aluminium construction, strong and light: only 19 kg!



Specifications

| Power input | 1.500 W |
|---------------|-----------|
| Voltage | 230V/50HZ |
| No load speed | 1.600 rpm |
| Net weight | 19 kg |
| Blade size | 255 mm |

Maximum cutting capacities in mm

| | 90° Cutting | 45° Miter cut |
|-------------|--------------------|----------------|
| Round | Ø 70 x 4 mm | Ø 60 x 4 mm |
| Square | 70 x 70 x 4 mm | 60 x 60 x 4 mm |
| Rectangular | 100 x 70 x 4 mm | 60 x 60 x 4 mm |



| Dry Miter Cutter 9410 ND | Ref. |
|---|--------|
| Dry Miter Cutter 9410 ND with 255/60T saw blade and fixation set "K" for tubes Ø 30 up to 70 mm | 600651 |

| Saw Blades | Ref. |
|--|-----------|
| CT saw blade 255/66T for stainless steel - food and construction | 600654NSF |
| CT saw blade 255/60T for mild steel | 600598 |
| CT saw blade 255/66T for thin steel | 600654 |
| CT saw blade 255/80T for aluminum | 600655A |
| LBS-saw blade 255/66T impact resistant | 72225566 |
| | |

| Accessories (optional) | Ref. |
|---|--------|
| Stand for the DMC 9410ND | 600599 |
| Fixation set "K" for tubes Ø 30 up to 70 mm | 600653 |

PERFORMANCE RELIABILITY COST-EFFECTIVENESS