

**LADO PARA USO EN PUERTA DERECHA  
THIS SIDE UP FOR LHR DOOR**

(2x) Marco de chapa / Hollow metal frame:

Perforar / Drill #25(3.75mm)

Marco de madera/Wood frame:

Perforar / Drill #25(3.75mm) Prof./Deep 1 1/4"(32mm)

MARCO O BORDE DE LA PUERTA SECUNDARIA  
FRAME STOP OR SECONDARY EDGE DOOR

PUERTA  
DOOR

18 (11/16")

(X6)Puerta de chapa / Hollow metal door: Perforar / Drill 1/8"(3.25mm)

Puerta de madera / Wood door: Perforar / Drill 1/8"(3.25mm) Prof./Deep 1/2"(12.5mm)

(X3)Perforar agujero pasante / Drill hole clearance 1/2"(12mm)  
(Solo en caso de uso de acceso exterior/ Only if usig an outside trim)

**T300 / T395**

**DISPOSITIVO ANTIPANICO TOUCH**

**RIM EXIT DEVICE**

(PLANTILLA PUERTA SIMPLE O PUERTA SECUNDARIA)  
(SINGLE DOOR TEMPLATE OR SECONDARY DOOR)

1300-87 REV.07 (11-2020)

40 (1 9/16")

MANUAL DE INSTRUCCIONES  
INSTRUCTION MANUAL



WWW.BLINCER.COM

DOBLAR AQUI / FOLD HERE

60 (2 3/8")

16 (5/8")

Linea central del antipánico y contrafrente  
Device & strike centerline

50 (1 31/32")

900 TO 1100 (36" TO 43")  
PARA PUERTAS DE ALTURA MAYOR A 2100mm USAR INSTALACION 1100mm  
FOR DOORS HIGHERS THAT 7' USE 43" HEIGHT CENTERLINE

VER MANUAL DE INSTALACION ANTES  
DE REALIZAR LAS PERFORACIONES  
SEE THE INSTALLATION MANUAL  
BEFORE DRILL THESE HOLES

PISO TERMINADO / FINISH FLOOR

31.5 (1 1/4")

23.5 (15/16")

40.5 (1 19/32")

CUIDADO- CAUTION  
NO UTILIZAR EN PUERTA DE VIDRIO  
DO NOT USE IN GLASS DOOR



POSICION DE AGUJEROS/HOLE LOCATIONS  
Y ( ) en pulgada.  
Primary dimensions are shown in mm,  
followed by inches ( ).



Blincer S.R.L Calle 127(Ombu)1444- San Martin-Prov. Bs. As.(Argentina)

Phone:+54 11 4712 5005 website: www.blincer.com

ADO PARA USO EN PUERTA DERECHA  
THIS SIDE UP FOR LHR DOOR

**LADO PARA USO EN PUERTA SECUNDARIA IZQUIERDA**  
**THIS SIDE UP FOR RHR SECONDARY DOOR**

BORDE DE PUERTA SECUNDARIA  
 EDGE OF SECONDARY DOOR

(2x) Marco de chapa / Hollow metal frame:  
 Perforar / Drill #25(3.75mm)

Marco de madera/Wood frame:  
 Perforar / Drill #25(3.75mm) Prof. / Deep 1 1/4"(32mm)

**PUERTA PRINCIPAL**  
**PRIMARY DOOR**

BORDE DE PUERTA PRIMARIA  
 EDGE OF PRIMARY DOOR

18 (1 1/16")

(X6) Puerta de chapa / Hollow metal door: Perforar / Drill 1/8"(3.25mm)  
 Puerta de madera / Wood door: Perforar / Drill 1/8"(3.25mm) Prof. / Deep 1/2"(12.5mm)

(X3) Perforar agujero pasante / Drill hole clearance 1/2"(12mm)  
 (Solo en caso de uso de acceso exterior/ Only if usig an outside trim)

**T300 / T395**  
**DISPOSITIVO ANTIPANICO TOUCH**  
**RIM EXIT DEVICE**  
 (PLANTILLA PUERTA DOBLE / DOUBLE DOOR TEMPLATE)  
 1300-87 REV. 07 (11-2020)

MANUAL DE INSTRUCCIONES  
 INSTRUCTION MANUAL



WWW.BLINCER.COM

UBICAR ESTA LINEA CON EL  
 BORDE DE LA HOJA SECUNDARIA  
 PLACE THIS LINE WITH EDGE OF  
 SECONDARY DOOR

9 (1 1/32")  
 17 (2 1/32")

40 (1 9/16")

8 (5/16")

Linea central del antipánico y contrafrente  
 Device & strike centerline

50 (1 31/32")

900 TO 1100 (36" TO 43")  
 PARA PUERTAS DE ALTURA MAYOR A 2100mm USAR INSTALACION 1100mm  
 FOR DOORS HIGHERS THAT 7' USE 43" HEIGHT CENTERLINE

VER MANUAL DE INSTALACION ANTES  
 DE REALIZAR LAS PERFORACIONES  
 SEE THE INSTALLATION MANUAL  
 BEFORE DRILL THESE HOLES

16 (5/8")

PISO TERMINADO / FINISH FLOOR

**CUIDADO / CAUTION**

NO UTILIZAR EN PUERTAS DE VIDRIO  
 DO NOT USE IN GLASS DOOR



POSICION DE AGUEROS/HOLE LOCATIONS

Y ( ) en pulgada.

Primary dimensions are shown in mm,  
 followed by inches ( ).



**LADO PARA USO EN PUERTA SECUNDARIA DERECHA**  
**THIS SIDE UP FOR LHR SECONDARY DOOR**

**Blincer S.R.L.** Calle 127(Ombu)1444- San Martin-Prov. Bs. As.(Argentina)

Phone:+5411 4712 5005 website: www.blincer.com