





TECNICAL INFORMATION

“Innovative permeable paver solutions are a necessity for the development of todays public spaces.” - Snøhetta


Asak
FLYT



ASAK FLYT 10
286x312x80 mm
Units per m²: 12,84
Weight per m²: 158,6kg



ASAK FLYT 17
286x312x80 mm
Units per m²: 12,84
Weight per m²: 148,3kg



ASAK FLYT 28
286x312x80 mm
Units per m²: 12,84
Weight per m²: 130,3kg

STANDARDS + PERFORMANCE

Description:	The Asak FLYT collection consists of three hexagonal interlocking pavers that can be combined to create seamless transitions when designing and programming outdoor spaces. Asak FLYT is permeable paving and a part of SuDS (sustainable drainage system). The collection has a unique flexibility and allows for a fluent permeable gradient from 10 – 28%. Perfect for use in urban spaces.
Installation:	Must be installed according to correct guidance for permeable paving.
Area of use:	Public outdoor spaces; pavements, parks, squares, housing associations, schoolyards etc.
Colors:	Standard grey. Other colors request
Impregnation/ surface treatment:	Not standard. Can be ordered with ClearNOx treatment. ClearNOx is a photocatalytic coating that removes air pollution when the surface gets exposed to sun/daylight (UV). It also makes the surface clean by removing organic stains. Read more on www.asak.no
Frost resistance:	≤1,0. Class 3 in according to NS-EN 1339,
Bending Strength:	5,0Mpa class 3. This pressure applies to all sizes and depths.
Wear resistance:	≤ 23
Slip / Skid resistance:	45 (Satisfactory)