




## TM TALL SERIES TMT75

The latest technology and design in rapid deploying shelters currently fielded with US military forces. UTS expeditionary military shelters benefit from an innovative system of deployment. The rapidly-deployable soft shelter incorporates a unique external folding-frame design and an internal liner system integrated with the outer fabric. The ease and speed with which our shelter systems deploy saves time and simplifies training. The innovative frame design and rope-and-pulley system provides a simple and easy to remember set-up procedure. Shelter setup times range from 5-15 minutes for all TM series shelters.



\*Shelter shown without thermal fly.

### USED FOR



MEDICAL FACILITIES



BASECAMPS & BILLETING



CBRN DEFENSE



DECON



COMMAND & CONTROL

### TESTED FOR



WIND



SNOW LOAD



DRIVING RAIN



BLACKOUT



ERECT & STRIKE

## FEATURES & BENEFITS

- **EASE OF DEPLOYMENT:** All of the TM Tall shelter models are rapid-deploying with average setup times between 5-15 minutes with minimal people and no tools or ladders. The setup procedures are simple and intuitive and require a minimal amount of training. This is all made possible because of the unique rope and pulley system. The systems allow the frame to be setup first allowing the fabric to be hoisted into place below the frame, eliminating the requirement to lift both the frame and fabric simultaneously. Having the frame external to the outer fabric allows for a thermal fly to be installed on top of the frame which creates additional environmental protection.
- **DURABILITY:** All aspects of the shelter are designed to be rugged and durable. The frame is built with robust components that are high strength offering trouble free setup. The fabric components are manufactured using the highest quality products with the most modern fabrication techniques.
- **PROVEN:** UTS shelters meet or exceed all DOD standards for environmental performance. Testing has been successfully completed for snow load, wind load, driving rain, blackout, durability, sand, dust, and salt fog.
- **MISSION READINESS:** Each UTS shelter comes equipped with integral ECU ducting, electrical outlets and remain inside the shelter during takedown and pack out. The optional lighting can also be left integral to the shelter during takedown and pack out.
- **MODULAR:** The shelters come in various sizes that can be interconnected to create larger complexes to meet the mission needs.
- **THERMAL EFFICIENCY:** The shelter has a very energy efficient design with a standard liner and thermal fly. Additional thermal efficiency can be achieved using the optional insulated liners.
- **SUPPORT:**
  - On sight delivery + free training
  - Refresher training
  - 24/7 Support in the field

©2023 UTS Systems, LLC

Current as of July 2022. Information subject to change without notice.


UTS Systems, LLC | 6051 North Lee Hwy, Fairfield, VA 24435

850.226.4301 | sales@uts-systems.com

uts-systems.com

102423

## DIMENSIONS



**NSN ORDERING #**

**6 DOOR**

**DT:** 8340-01-691-9833

**OD:** 8340-01-692-0013

**6 DOOR**

<b>PART NUMBERS</b>	DESERT TAN	UTMT75M1-DT
	O.D. GREEN	UTMT75M1-OD
	COYOTE BROWN	UTMT75M1-CB
<b>INTERIOR DIMENSIONS</b>	20.7 x 42.0 x 8.5 Eave, 10.8 Peak	
<b>USEABLE FLOOR SPACE</b>	882 ft <sup>2</sup>	
<b>DEPLOYMENT TIME</b>	Setup with 10 people in 10-15 minutes	
<b>STRIKE TIME</b>	Strike with 10 people in 10-15 minutes	
<b>PORTABILITY/WEIGHT (IN BAGS)</b>	Tent Fabric: 476 lbs (incl. Insulated Liner, Floor & Repair Kit) Roof Frame: 275 lbs Side Arches: 116 lbs Thermal Fly: 116 lbs Staking Kit: 70 lbs <b>Total Weight: 1,053 lbs</b>	
<b>PACKED DIMENSIONS (L X W X H INCHES)</b>	Tent Fabric: 87 x 45 x 30 Roof Frame: 93 x 13 x 22 Side Arches: 93 x 25 x 5 Thermal Fly: 39 x 35 x 15 <b>Total Volume: 94 ft<sup>3</sup></b>	
<b>COMPLEXING</b>	End Doors, End Walls, (optional) Side Doors	
<b>PASS-THROUGH PORTS/ SLEEVES</b>	ECU/Cable ducts on both end walls	
<b>WINDOWS</b>	Standard	
<b>SHELTER MATERIAL &amp; SUB-FLOOR</b>	Meets MIL-PRF-44103	
<b>HANGING MECHANISMS</b>	100 lbs each; Interior Hang Points	
<b>INTERIOR ELECTRICAL</b>	Standard Equipment; Interior shelter cord with lighted triple tap	