

## FE-SPK-IPC2

Classic wooden classroom speaker, FE-SPK-IPC2 is an active PoE+ SIP-speaker. Able to connect to any SIP-server as standard SIP-client and get a phone call as standard SIP-extension. Simple to install and set up. Audio files and voice messages can be streamed live or uploaded to device to play them later or periodically from build-in timer/scheduler. Auto-provisioning through IP-INTEGRA SIP server saves time, especially in the case of large-scale installations. The module can easily be integrated with 3<sup>rd</sup> party SIP systems through WEB interface.



## At a first glance

- EN 54-24 Certification
- Ball-proof according to DIN 18032
- User-friendly WEB interface for Remote Setup
- Full range speaker
- Designed for wide response (music and speech)
- Self-diagnosing and reporting through e-mail
- Wooden cabinet with protective metal grille
- Easy wall mounting via supplied mounting bracket and accessories



Specification

HARDWARE

Ethernet connector 1x RJ 45

Power Options PoE and/or external PS 5V/1.5A DC

PoE IEEE 802.3at

Power Consumption Idle: 1.8W / Max: 20W (Volume dependant)
CPU Allwinner H2+, Quad-core Cortex A-7

**NETWORKING AND PROTOCOLS** 

Protocols IPv4 (with DiffServ), SIP, TCP, UDP, HTTP, RTP, DHCP, SNMP, NTP

LAN Protocols PoE (802.3at) Network Access Control (802.1x)

Management and operation HTTP (Web Configuration) DHCP and Static IP, Remote Software upgrade, Centralized

monitoring

SIP Support RFC3261 (SIP Base Standard), RFC3515 (SIP Refer), RFC2976 (SIP Info), SIP using

TLS, RFC5630 SIPS Uri scheme

DTMF Support RFC2833, 2976 (SIP Info)

OTHER SPECIFICATIONS

Input 1x I/O PIN

5V DC and 12V DC

Output 3x Open-Controller @ 2A, up to 15V (LED RGB Button drive)

Microphone Yes

SPEAKER SPECIFICATION

 $\begin{array}{lll} \mbox{Rated Power} & 10 \ \mbox{W} \\ \mbox{Impedance} & 10 \ \mbox{\Omega} \\ \mbox{SPL (1W/1m)} & 93 \ \mbox{dB} \\ \mbox{MAX SPL (Rated W/1m)} & 100 \mbox{db} \\ \end{array}$ 

Frequency range (-10dB) 100 Hz to 19 kHz

Dispersion 1 kHz / 4 kHz 175° / 65°

Operating temperature -30°C to +60°C

Power Selection PoE+

Material Housing: Steel

Colour and finish White

Dimensions 265x165x90 (HxWxD)

Net Weight 2kg Mounting Screws